



The photograph may not match the reference exactly. Please read the product description to identify the finish.

### TECHNICAL CHARACTERISTICS



Product Model:	D-191HLED80-36		D-191HLED60-24		D-191HLED30-16		D-191HLED40-56B	D-191HLED60-84B
IP Protection degrees:	IP66		IP66		IP66		IP66	IP66
IK Protection degrees:	IK09		IK09		IK09		IK09	IK09
Light source:	36 X CREE LED 80W Warm White - 4000K 8400Lm <sup>(N)</sup> CRI 70	36 X LUXEON 5050 80W Warm White - 4000K 10240Lm <sup>(N)</sup> CRI 70	24X CREE LED 60W Warm White - 4000K 6300Lm <sup>(N)</sup> CRI 70	24X LUXEON 5050 60W Warm White - 4000K 7680Lm <sup>(N)</sup> CRI 70	16 X CREE LED 30W Warm White - 4000K 3150Lm <sup>(N)</sup> CRI 70	16X LUXEON 5050 30W Warm White - 4000K 3840Lm <sup>(N)</sup> CRI 70	16X LUXEON 3030 40W Warm White - 4000K 4600Lm <sup>(N)</sup> CRI 70	16X LUXEON 3030 60W Warm White - 4000K 6850Lm <sup>(N)</sup> CRI 70
Total power consumption(W):	80		60		30		40	60
Voltage/Frequency:	100-240V/50-60Hz		100-240V/50-60Hz		100-240V/50-60Hz		100-240V/50-60Hz	100-240V/50-60Hz
Warranty(Years):	5		5		5		5	5
Units per box	1		1		1		1	1

### MATERIALS / FINISHES

<b>Structure material:</b> High purity aluminium	<b>aiffuser material:</b> Glass
<b>Structure finish:</b> Silver	<b>Diffuser finish:</b> Transparent

### GEAR

Multi-voltage electronic gear included (100-240 V / 50-60 Hz)

