



N-01~N-03

Inwater lighting



N-01
6W




N-02
18W



N-03
40W

简述 Description



- 316不锈钢灯体外壳及面板
- 高强度钢化玻璃，确保过IK08标准测试要求
- 多种光学配件选项，具有高视觉舒适性和防眩效果
- 灯具光源模组角度可调
- 无生物蓝光危害风险，符号EN62471: 2008 标准
- 所有外部螺钉均为316不锈钢材质

- 316 stainless steel body and frame.
- Higher hardened tempered glass, it ensure pass IK08 standard test.
- Multiple optics options, it with high visual comfort and good anti glare effect.
- LED module the angle adjustable.
- No photo-biological risk, in accordance with EN 62471:2008.
- All external screw are in 316 stainless steel.

功率: 6W / 18W / 40W
光效: 90-110 Lm/W
色温: 3000K / 4000K / RGBW
输入电压: DC 24V
功能选项: Switch / DMX

Power: 6W / 18W / 40W
Nominal efficacy: 90-110 Lm/W
CCT: 3000K / 4000K / RGBW
Input voltage: DC 24V
Options: Switch / DMX



- 应用场合: 水族馆、水池雕塑、广场喷泉、游泳池等场所
- Applications: Aquatic animals exhibition halls, water pool sculptures, fountains, swimming pools etc.

N-01~N-03


Inwater lighting



发光角度 Optics




技术参数 Technology data




N-01

| Code | Power | LED Qty | Control Options | Input Voltage | Optics | Packing Size | Weight |
|-----------------------|-------|----------|-----------------|---------------|-----------|------------------|--------|
| LED chips - 3535 | | | | | | | |
| N-01LED6-3 | 6W | 3 | Switch | DC 24V | 25° / 50° | 370*250*150/6pcs | 7 |
| LED chips - RGBW | | | | | | | |
| N-01LED6-3RGBW | 6W | 3 | DMX | DC 24V | 25° / 50° | 370*250*150/6pcs | 7 |



N-02

| Code | Power | LED Qty | Control Options | Input Voltage | Optics | Packing Size | Weight |
|------------------------|-------|----------|-----------------|---------------|-----------|------------------|--------|
| LED chips - 3535 | | | | | | | |
| N-02LED18-9 | 18W | 9 | Switch | DC 24V | 25° / 50° | 350*300*155/4pcs | 10.2 |
| LED chips - RGBW | | | | | | | |
| N-02LED18-9RGBW | 18W | 9 | DMX | DC 24V | 25° / 50° | 350*300*155/4pcs | 10.2 |



N-03

| Code | Power | LED Qty | Control Options | Input Voltage | Optics | Packing Size | Weight |
|-------------------------|-------|-----------|-----------------|---------------|-----------|------------------|--------|
| LED chips - 3535 | | | | | | | |
| N-03LED40-18 | 40W | 18 | Switch | DC 24V | 25° / 50° | 360*180*155/2pcs | 6.6 |
| LED chips - RGBW | | | | | | | |
| N-03LED40-18RGBW | 40W | 18 | DMX | DC 24V | 25° / 50° | 360*180*155/2pcs | 6.6 |