



The photograph may not match the reference exactly.
Please read the product description to identify the finish.

TECHNICAL CHARACTERISTICS



Product Model:	T-05LED40-24	T-05LED50-32	T-05LED60-32
IP Protection degrees:	IP66		
IK Protection degrees:	IK08		
Light source:	24 x LED CREE / 24 x LUXEON 5050	32 x LED CREE / 32 x LUXEON 5050	32 x LED CREE / 32 x LUXEON 5050
Total power consumption:	40W	50W	60W
Luminous Flux:	2800-3200Lm	3700-4000Lm	4300-4800Lm
Luminous efficiency:	70-80Lm/w		
Color temperature:	4000K as standard. Optinal 2700K, 3000K & 5700K. Amber LED available		
Voltage/Frequency:	100-240V/50-60Hz		
Warranty(Years):	5		
Units per box:	1		
Net Weight(Kg)	8.5		
Aerodynamic resistance (CxS)	0.17		

MATERIALS / FINISHES

Structure material: High purity aluminium	aiffuser material: PC diffuser
Structure finish: Black	Diffuser finish: Matt

GEAR

Multi-voltage electronic gear included (110-240 V / 50-60 Hz)

Lm^(N): Nominal flow of light in actual working conditions. Its actual flow will depend on the environmental conditions and the efficiency of the optics and/or diffuser.

Kled reserves the right to make the necessary technical changes they deem adequate, in order to improve the features of the product.
Please consult the sales team to clarify any doubt.

Tel.: +86 574 62566 890
Email: info@kled.com.cn
http://www.kled.com.cn/

