



The photograph may not match the reference exactly. Please read the product description to identify the finish.

TECHNICAL CHARACTERISTICS



Product Model:	T-91LED(MD06)40-24	T-91LED(MD06)60-24	T-91LED(MD06)60-32	T-91LED(MD06)80-32
IP Protection degrees:	IP65	IP65	IP65	IP65
IK Protection degrees:	IK08	IK08	IK08	IK08
Light source:	24 x LED CREE	24 x LED CREE	32 x LED CREE	32 x LED CREE
Total power consumption:	40W	60W	60W	80W
Luminous Flux:	4200Lm	6000Lm	6480Lm	8400Lm
Luminous efficiency:	100-108Lm/w			
Color temperature:	4000K as standard. Optinal 2700K,3000K & 5700K. Amber LED available			
Voltage/Frequency:	100-240V/50-60Hz			
Warranty(Years):	5			
Units per box:	1			
Net Weight(Kg)	5.8	5.8	6.1	6.2

MATERIALS / FINISHES

Structure material: High purity aluminium	aiffuser material: PC diffuser
Structure finish: Black	Diffuser finish: Matt

GEAR

Multi-voltage electronic gear included (100-240 V / 50-60 Hz)

Lm^(N): Nominal flow of light in actual working conditions. Its actual flow will depend on the environmental conditions and the efficiency of the optics and/or diffuser.

