



The photograph may not match the reference exactly. Please read the product description to identify the finish.

**TECHNICAL CHARACTERISTICS**



Product Model:	TG-201LED440-144	TG-201LED600-216	TG-201LED660-216	TG-201LED720-216
IP Protection degrees:	IP66			
IK Protection degrees:	IK09			
Light source:	144 x 5050	216x 5050		
Total power consumption:	440W	600W	660W	720W
Luminous Flux:	54700-61500Lm	68500-81700Lm	74500-86000Lm	80500-91300Lm
Luminous efficiency:	115-140Lm/w			
Color temperature:	4000K as standard. Optinal 2700K,3000K & 5700K. Amber LED available			
Voltage/Frequency:	100-240V/50-60Hz			
Warranty(Years):	5			
Units per box:	1			
Net Weight(Kg)	25	26	26	27
Aerodynamic resistance (CxS)	0.28			

**MATERIALS / FINISHES**

<b>Structure material:</b> High purity aluminium	<b>Diffuser material:</b> Glass
<b>Structure finish:</b> Gray	<b>Diffuser finish:</b> Transparent

**GEAR**

Multi-voltage electronic gear included (100-240 V / 50-60 Hz)

Lm<sup>(N)</sup>: Nominal flow of light in actual working conditions. Its actual flow will depend on the environmental conditions and the efficiency of the optics and/or diffuser.

Kled reserves the right to make the necessary technical changes they deem adequate, in order to improve the features of the product. Please consult the sales team to clarify any doubt.

Tel.: +86 574 62566 890  
Email: info@kled.com.cn  
http://www.kled.com.cn/

High purity aluminium



Ultra-white glass

installation template