

**B-140**

6W



**B-140D**

6W\*2


简述 Description



- 铝压铸盖帽，铝合金拉伸灯体，可根据需要截取不同高度
- 高透明PC扩散罩，能有效防止发黄老化，并具有很好的出光视觉效果
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可以达到1000小时以上
- 无生物蓝光危害风险，符号EN62471: 2008 标准
- 灯具表面最高温度不超过50度，安全可靠

- Aluminum die casting cover, extruded aluminum alloy body, it can be cut different heights.
- High transparent PC diffuser, it can effectively prevent yellowing and aging. with high visual comfort light distribution.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, in accordance with EN 62471:2008.
- The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.

技术参数 Technology data



**B-140**

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 2835							
<b>B-140LED6-48B</b>	6W	<b>48</b>	100V-240V	450	100°	385*320*300	8
<b>B-140DLED12-96B</b>	12W	<b>48*2</b>	100V-240V	900	100°	385*320*300	8

延伸产品 More in family



**C-140**

Bollard Lighting: 10W / 15W.  
Page. 386



**C-140D**

Bollard Lighting: 15W / 25W.  
Page. 386