





简述 Description



- 铝压铸灯体外壳，铝合金拉伸灯杆，高度根据客户需要截取
  - 模组式光源模块配超白钢化玻璃，具有很好的光舒适性
  - 防紫外线聚氨酯粉喷涂表面，耐腐蚀可以达1000小时以上
  - 灯具表面最高温度不超过50度，安全可靠
  - 所有外部螺钉均为304不锈钢材质，底座埋件额外可选配
- Aluminum die casting cover, extruded aluminum body, it can be cut different height.
  - LED module design and with supper tempered galss, It has more comfortable light effect.
  - Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
  - The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.
  - All external screws are made of 304 stainless steel, Additional optional base embedded parts.


配光曲线 Photometric Data



技术参数 Technology data

| Code               | Power | LED Qty | Input Voltage | Packing Size      | Weight |
|--------------------|-------|---------|---------------|-------------------|--------|
| LED chips - 5050   |       |         |               |                   |        |
| C-231ALED15-5-H80  | 15W   | 5       | 100V-240V     | 830*385*380/4pcs  | 14.8   |
| C-231ALED15-5-H100 | 15W   | 5       | 100V-240V     | 1030*385*380/4pcs | 17.8   |
| LED chips - 5050   |       |         |               |                   |        |
| C-231BLED15-5-H80  | 15W   | 5       | 100V-240V     | 830*285*290/4pcs  | 14.8   |
| C-231BLED15-5-H100 | 15W   | 5       | 100V-240V     | 1030*285*290/4pcs | 17.8   |

延伸产品 More in family



T-231A / T-231B / T-231C

Residential Lighting: 40W / 80W / 120W.  
Page. 206

可选配件 Accessories options

|                         | Code      |
|-------------------------|-----------|
| 装饰盖 Decorative Cover    | 220001875 |
| Q-02H防水连接器 Terminal Box | 320000698 |
| 基础预埋件 Anchor Bolts      | 250000377 |
| 膨胀螺钉 Expansion Bolts    | 613040003 |