


M-01A
2W



M-01B
1W

简述 Description



- 铝压铸灯体外壳，高强度透明PC扩散罩
- 侧向单侧发光和双侧发光方式，具有高视觉舒适性和防眩效果
- 耐高温防水硅胶圈、耐腐蚀PP塑料埋件
- 根据需要地板 / 地面 / 墙面嵌入式安装应用
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 所有外部螺钉均为304不锈钢材质

- Die-casting aluminium body, high quality pc diffuser.
- Side radial light with unilateral & bidirectional emission, it with high visual comfort and good anti glare effect.
- High temperature resistant and waterproof silicone rubber ring, corrosion resistant PP plastic installion housing.
- Floor/ground/wall-mounted recessed luminaire intended applications as required.
- No photo-biological risk, in accordance with EN 62471:2008.
- All external screw are made of 304 stainless steel.



Ground installation




Floor installation



Wall-mounted installation


光效: 60-70 Lm/W (Ra80)
色温: 3000K / 4000K / BLUE
Nominal efficacy: 60-70 Lm/W (Ra80)
CCT: 3000K / 4000K / BLUE

技术参数 Technology data



M-01A

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 2835 M-01ALED2-8	2W	8	Switch	24V AC/DC	120°	360*245*250/12pcs	6.5



M-01B

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 2835 M-01BLED1-4	1W	4	Switch	24V AC/DC	120°	360*245*250/12pcs	6.5