



简述 Description




- 铝压铸盖帽，铝合金拉伸灯体，可根据需要截取不同高度
- PC棱纹透明罩，具有高视觉舒适性和均匀配光透镜
- 灯具具有常规供电和太阳能供电2个版本供选择
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可达1000小时以上
- 灯具表面最高温度不超过50度，安全可靠

- Aluminum die casting base and heatsink, extruded aluminum alloy body.
- PC prism transparent diffuser with high visual comfortable and uniform lighting distribution.
- There are two version design: AC input normally version and solar version.
- Surface anti-ultraviolet pure polyester powder painting.
- The maximum surface temperature of all accessible part under 50 degrees.

其他功能选项: 移动感应功能 / 双色温切换功能  
 Other Options: Move sensor options / Colour temperature options


配光曲线 Photometric Data



技术参数 Technology data

Code	Power	LED Qty	Input Voltage	Packing Size	Weight
LED chips - 2835					
C-142LED12-60H65	12W	60	100V-240V	675*230*190	3.2
LED chips - 2835, With Solar					
C-142LED3-25H65	2.5W/0.1W	25	SOLAR+SENSOR	675*230*190	3.2

延伸产品 More in family



可选配件 Accessories options

	Code
防水接线盒 Terminal Box	23000232
膨胀螺钉 Expansion Bolts	61304003