




B-201



B-201
25W

简述 Description




- 铝压铸灯体外壳，布纹钢化玻璃，具有高视觉舒适性和均匀光输出
- 高性能LED芯片，驱动有0-10V / DALI / 编程电源选择
- 灯具采用LED 模组式设计，模块式电器部件，安装更换方便
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可以达到1000小时以上
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 灯具表面最高温度不超过50度，安全可靠

其他功能选项:
微波感应功能 / 应急功能 / 双色温切换功能

- Die-casting aluminium body, prism super tempered glass, with high visual comfort and uniform lighting distribution.
- High quality LED chips, Driver with 0-10V/DALI/programmed options.
- LED module designed, Integrated components which is easy to install and replace.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, (no risk linked to infrared, blue light and UV radiation) in accordance with EN 62471:2008.
- The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.

Other Options:
Microwave options / Emergency options / Colour temperature options

技术参数 Technology data



B-201

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 2835 B-201LED25-132	25W	132	100V-240V	2360	100°	410*335*310	2